



INSTALLATION INSTRUCTIONS

Unitronic UniFLEX Hardware Kit for 2.5TFSI® EVO (w/o Sensor) UH010-FLA

Unitronic recommends that you read through the entire installation instructions prior to beginning the installation to familiarize yourself with the included components, tools required, and procedures involved with the installation.

DISCLAIMER: Unitronic recommends that a Unitronic Authorized Dealer or other qualified and trained professional should perform the installation of this product.

Unitronic Installation Instructions are also available in digital format, if you prefer. Please visit the corresponding product page for a link to download the digital Installation Instructions. www.getunitronic.com

It is recommended to confirm all parts are present prior to beginning the installation.

PACKING LIST:

PART NUMBER	DESCRIPTION	QUANTITY INCLUDED
UH026-FL7	UniFlex Sensor Harness	1
UH027-FL7	UniFlex 8V RS3® & 8S TTRS® Body Harness	1
UH019-TL2	UniFlex Ethanol Device	1

RECOMMENDED TOOLS NEEDED:

- 7mm socket
- 1/4" Ratchet
- T25 Socket
- Clamp Pliers



FIG. A



INSTALLATION INSTRUCTIONS

Unitronic UniFLEX Hardware Kit for 2.5TFSI® EVO (w/o Sensor) UH010-FLA

- 1** To start the installation, first remove the engine cover by lifting up on the 4 corners of the cover. (See Fig. 1)
- 2** Using the 7mm socket and ratchet wrench, loosen the screw clamp maintaining the flex coupling to the intake box. (See Fig. 2)
- 3** Using clamp pliers, remove the diverter valve spring clamp located on the engine air intake box. (See Fig. 3)
- 4** Once the clamp is removed to the lower part of the hose disconnect the hose from the intake box. (See Fig. 4)
- 5** Now locate the front air duct located in front of the airbox and unscrew the 2X T25 screws holding it in place. (See Fig. 5)
- 6** Once the two T25 screws are removed push the air duct backwards into the airbox and tilt the front up and pull out the air duct. (See Fig. 6)
- 7** When the air duct is removed pull upwards on the airbox to release it from the rubber grommets. Rotate at an angle to get it out of the flex coupling and remove the airbox from the car. (See Fig. 7)
- 8** Right below the position of the airbox locate the wiring harness clipped into the plastic rail. (See Fig. 8)



FIG. 1



FIG. 2



FIG. 3



FIG. 4



FIG. 5



FIG. 6




FIG. 7



FIG. 8



INSTALLATION INSTRUCTIONS

Unitronic UniFLEX Hardware Kit for 2.5TFSI® EVO (w/o Sensor) UH010-FLA

- 9** Locate the black 8 pin connector and unclip it from the plastic rail. (See Fig. 9)
- 10** Pull the tab carefully and unclip the connector. (See Fig. 10)
- 11** Locate the longer body harness (UH027-FL7) and plug it in between the OEM connector like a Y connection. (See Fig. 11)
- 12** With the body harness plugged in correctly, clip in the plastic pin into the lower bracket hole next to the larger gray connector and tuck away the other side of the connector under the headlight housing. (See Fig. 12)
- 13** Continue by routing the harness under the hood latch cable and zip tie it as shown here. (See Fig. 13)
- 14** Tuck the harness along the top of the rad support below the air duct openings and above the hood latch mechanism as shown. (See Fig. 14)
- 15** On the passenger side of the car, zip tie the harness the same way with the hood latch cables. (See Fig. 15)
- 16** Route the remaining part of the harness near the headlight housing and module as shown in this image. (See Fig. 16)



FIG. 9




FIG. 10




FIG. 11



FIG. 12



FIG. 13



FIG. 14



FIG. 15




FIG. 16



INSTALLATION INSTRUCTIONS

Unitronic UniFLEX Hardware Kit for 2.5TFSI® EVO (w/o Sensor)
UH010-FLA

- 17** Locate the UniFLEX module. Using Velcro or double sided tape, install the UniFLEX device on the side of the passenger side headlight module.
DO NOT MOUNT THE MODULE NEAR ANY RADIANT HEAT SOURCES. (See Fig. 17)
- 18** Locate the shorter (UH026-FL7) Flex Sensor Harness and connect it to the UniFlex module on one end and to your ethanol content sensor on the other end. Zip tie the sensor harness to the protected section of the fuel line or depending where your sensor is installed to any available supports. (See Fig. 18)
- 19** Reinstall the intake system in reverse order of disassembly.

CONGRATULATIONS! You have successfully installed Unitronic's UNIFLEX device and harness!

Download the UniE85 App Now!




FIG. 17



FIG. 18