

INSTALLATION INSTRUCTIONS

Unitronic Feature Box for UAF Control UH025-ACA

Unitronic recommends that you read through the entire installation instructions prior to beginning the installation to familiarize yourself with the included components, tools required, and procedures involved with the installation.

DISCLAIMER: Unitronic recommends that a Unitronic Authorized Dealer or other qualified and trained professional should perform the installation of this product.

Unitronic Installation Instructions are also available in digital format, if you prefer. Please visit the corresponding product page for a link to download the digital Installation Instructions. www.getunitronic.com

It is recommended to confirm all parts are present prior to beginning the installation.


PACKING LIST:

Part Number	Description	Quantity
UH025-ACA	Unitronic Feature Box for UAF Control	1
UH037-FL7	Wiring Harness for FeatBox	1

RECOMMENDED TOOLS NEEDED:

- 1. 90-Degree pick
- 2. Side cutters


1 . Open the engine compartment of the vehicle.




2. Remove the weather stripping on the rain tray



- 3. The rain tray is split into two sections. To complete the installation, the left side (Passenger Side) will need to be removed.
- 4. To remove the left side of the rain tray, carefully lift up the top left corner of the rain tray to unclip it from the windshield.



5. Locate the soundaktor in the middle of the cowl



6. Under the soundaktor, there is a 6-pin connector with a locking tab. This will be difficult to remove since the locking tab will need to be unlocked before the connector can be removed. To unlock the tab, it will need to be slid towards the right side of the vehicle (Driver Side). A 90 Degree pick can be used to unlock the tab.




7. With the 6-pin connector removed, locate the UH037-FL7 (Unitronic Feat Box Wiring Harness). This harness will have three Connectors.

**The connector circled in red will plug into the vehicle.

**The connector circled in Yellow will plug into the vehicle's 6-Pin connector that was removed in the step above

** The connector circled in blue will connect to the Unitronic UAF box.



8. With the feature box plugged in and securely mounted to the chassis using zip ties, reinstall the engine bay plastics in reverse order of removal

CONGRATULATIONS! You have successfully installed Unitronic's Feature Box.

Please follow this link to download the Unitronic UAF Control mobile application for Android or iOS devices. You will be prompted to create an account utilizing the email provided at the time of purchase. Once logged in, put the vehicle in accessory mode or start the engine to power up the Feature Box, in order for your phone to detect it via Bluetooth.