

INSTALLATION INSTRUCTIONS

Unitronic FeatureBox for UAF Control UH025-ACA

Unitronic recommends that you read through the entire installation instructions prior to beginning the installation to familiarize yourself with the included components, tools required, and procedures involved with the installation.

DISCLAIMER: Unitronic recommends that a Unitronic Authorized Dealer or other qualified and trained professional should perform the installation of this product.

Unitronic Installation Instructions are also available in digital format, if you prefer. Please visit the corresponding product page for a link to download the digital Installation Instructions. www.getunitronic.com

It is recommended to confirm all parts are present prior to beginning the installation.


PACKING LIST:

Part Number	Description	Quantity
UH025-ACA	Unitronic FeatureBox for UAF Control	1
UH037-FL7	Wiring Harness for FeatBox	1

RECOMMENDED TOOLS NEEDED:

- 1. 90-Degree pick
- 2. Side cutters


1 . Open the engine compartment of the vehicle.




2. Remove the weather stripping on the rain tray




3. **For the MK8 GTI and Golf R:** The rain tray is split into two sections. To complete the installation, the left side (Passenger Side) will need to be removed.



4. To remove the left side of the rain tray, carefully lift up from the top left corner to unclip it from the windshield and locate the SoundAktor module in the middle of the cowl.



5. For the 8Y S3 and RS3: The rain tray will not split into two sections. The rain tray needs to be lifted in the top left corner to access the SoundAktor Module.



6. The Soundaktor Module will be located on the left side under the cowl.



7. For the MK8 GTI and Golf R: There is a 6-pin connector with a locking tab beneath the SoundAktor module. This will be difficult to remove since the locking tab will need to be unlocked before the connector can be removed. To unlock the tab, it will need to be slid towards the right side of the vehicle (Driver Side). A 90 Degree pick can be used to unlock the tab.



8. For the 8Y S3 and RS3: The SoundAktor module can be removed from the tray it rests in. To remove the module, there is a tab at the front of the tray that will need to be pulled towards the front of the vehicle. When the tab is being held open, push down on the back where the 6-pin connector is located to lift the module out of the tray. Remove the 6-pin connector from the module by unlocking the gray tab and removing the connector.



9. With the 6-pin connector removed, locate the UH037-FL7 (Unitronic Feat Box Wiring Harness). This harness will have three connectors.



- The connector circled in red will plug into the vehicle.
- The connector circled in yellow will plug into the vehicle's 6-Pin connector that was removed in the step above.
 - The connector circled in blue will connect to the Unitronic FeatureBox.
- 10. With the FeatureBox plugged in and securely mounted to the chassis using zip ties, reinstall the engine bay plastics in reverse order of removal.

CONGRATULATIONS! You have successfully installed Unitronic's FeatureBox.

Please follow this link to download the Unitronic UAF Control mobile application for Android or iOS devices. You will be prompted to create an account utilizing the email provided at the time of purchase. Once logged in, put the vehicle in accessory mode or start the engine in order for your phone to detect the FeatureBox via Bluetooth and follow the on-screen prompts.