

INSTALLATION INSTRUCTIONS

Unitronic Resonator Delete for MK7/MK7.5 Golf R & 8V/8V.2 A3/S3 **UH084-EXA**

Unitronic recommends that you read through the entire installation instructions prior to beginning the installation to familiarize yourself with the included components, tools required, and procedures involved with the installation.

DISCLAIMER: Unitronic recommends that a Unitronic Authorized Dealer or other qualified and trained professional should perform the installation of this product.

Unitronic Installation Instructions are also available in digital format, if you prefer. Please visit the corresponding product page for a link to download the digital Installation Instructions. www.getunitronic.com

It is recommended to confirm all parts are present prior to beginning the installation

PACKING LIST:

Part Number	Description	Quantity
UH025-EX5	Unitronic Resonator Delete	1
UH019-EX0	Stainless Steel Clamp, 63.5mm	1
UH020-EX0	Stainless Steel Clamp, 70mm	1

RECOMMENDED TOOLS NEEDED:

- 3/8 Drive Impact
- 13mm Socket
- Exhaust Pipe Cutting Tool
- Exhaust Hanger Pliers





INSTALLATION INSTRUCTIONS

Unitronic Resonator Delete for MK7/MK7.5 Golf R & 8V/8V.2 A3/S3 UH084-EXA

- 1 Secure your vehicle on a hoist to gain access to the underside of the vehicle.
- 2 Using an exhaust pipe cutting tool, make a cut after the resonator approximately 105mm from the exhaust hanger bracket. (See Fig. 1)
- Once done, remove the front clamp using a 13mm socket.
- 4 Using exhaust hanger pliers, remove the resonator from the hanger. Slip the factory part out of the cat-back and set it aside.
- Position the Unitronic Resonator Delete in place, installing the 63.5 mm butt-joint band clamp at the front and the 70 mm butt-joint band clamp at the rear. (See Fig. 2).
- 6 Make sure to reattach the hanger bracket to the hanger mount. (See Fig. 3)







FIG. 1 FIG. 2 FIG. 3

CONGRATULATIONS! You have successfully installed Unitronic's MK7/7.5 Golf R + 8V/8V.2 A3/S3 Resonator Delete Kit.

